



CARLI PLAC

ULTRA MDO

The best plywood in the world

POWERED BY



CARLI PLAC ULTRA® MDO CONCRETE FORM

SUPERIOR SPECIFICATION FOR OUTSTANDING PERFORMANCE



✓ Two steps process

CARLI PLAC ULTRA® MEDIUM DENSITY OVERLAY CONCRETE FORM

MDO (Medium Density Overlay) is produced with a high-quality thermosetting resin-impregnated fiber surface bonded to one or both sides under heat and pressure to create an exterior-grade plywood panel.

- ✓ Easy to form
- ✓ Smooth and flat surface

CARLI PLAC
ULTRA MDO

CARLI PLAC ULTRA® MDO CONCRETE FORM

SPECIFICATIONS

Two-Step Process
Paper and veneer are pressed in a two step process
Minimum grain transfer
Matte finish

Thickness	Average Pour Range
12mm 5 plies	Up to 4 Pours*
15mm 5 plies	* The numbers of pours will vary based on job site conditions and panel handling.
18mm 7 plies	
Standard panel size 2440mm x 1220mm	




CARLI PLAC ULTRA® MDO CONCRETE FORM



12mm - 75 PC UNIT
15mm - 60 PC UNIT
18mm - 50 PC UNIT

ULTRA® MDO CONCRETE FORM
SHOWS MINIMAL GRAIN TRANSFER





CARLI PLAC

ULTRA MDO

 **+55 42 3624.5400**

  **/CARLIPLAC_PLYWOOD**

 **CARLIPLAC.IND.BR**